



CE52LH1WP

- Fully approved IP66 weather resistant
- Screen Size 52 inch (132 cm), Full HD
- Contrast ratio 1,500 : 1, brightness 500 cd/m²
- Vandalism- and tamper-proof anti-reflective glass
- Winter mode: Guaranteed monitor usability at temperatures ranging from -20 °C to +45 °C
- Ideally suited for various indoor and outdoor installations as well as 24/7 applications
- Anti-corrosive anodized aluminium cabinet

FEATURES

- 52" LCD fully sealed IP66 rated weatherproof monitor
- Protected against powerful water jets and short term flooding
- Fully approved oil, smoke and dust protected
- Vandalism and tamper proof anti-reflective glass
- Anti-corrosive anodized aluminium cabinet
- Network integration optional for control over LAN
- Impressive picture quality: HD Ready
- Superior data scaling for PC connectivity
- Upgraded scaler for PC operation
- 24hour / 7day approved
- Extensive input & output terminals
- Powersave mode
- Wintermode operation to -20C temp
- Portrait mode



Weatherproof
Outdoor LCD Panel

AUDIO VISUAL SPECIFICATION

LCD Screen Size	52" (132cm)
Active Screen Area	115.2 x 64.8 mm
Aspect Ratio	16:9
Native Resolution	1920 x 1080 (HDTV 1080p)
Pixel Pitch	0.2 x 0.6 mm
Grey scale value	8 bit
Number of colours	16.7 M
Brightness	500 nits
Contrast Ratio	1,500:1
Viewing angle H/V	176°
Response time	6.5 ms
Colour System	PAL, NTSC3.58 (AV in), SECAM
Computer compatibility	UXGA/WXGA/SXGA/XGA/SVGA/VGA

POWER

Voltage in	100-240V 50/60Hz
Power Consumption	290W, 2W standby

DIMENSIONS AND MOUNTING

Dimensions	1,304 x 800 x 234.5 mm
Weight	74 kg
Vesa mounting	420 x 516 mm, 997 x 420 mm
Colour of cabinet	Silver

AUDIO VISUAL CONNECTION

Input Terminals	DVI-D (digital/HDCP)
	D-Sub15
	5 x BNC (RGBHV, Y-Pb/Cb-Pr/Cr)
	Component (Y, Pb, Pr)
	BNC (Video)
	Scart (RGB)
	Video
	RS232 (D-Sub 9 pin)
	2 x RCA (R/L mono) for Audio
	3.5 mm Stereo Jack for Audio
Output Terminals	5 x BNC (RGBHV, Y-Pb/Cb-Pr/Cr)
	Component (Y, Pb, Pr)
	BNC (Video)
	RS232 (D-Sub 9 pin)
	2 x RCA (R/L mono) for Audio
	External speaker output (2 x 10 W)
	PJ Network integration option

ENVIRONMENTAL PERFORMANCE

Resistant to	Water, Steam, Smoke, Oil and Dust
Rated Protection	IP66, strong jets of water
Rated Protection	IP66, totally protected against dust
Operating Temp	-20C to +45C (wintermode operation)
Storage Temp	-20 to +60C

